

OMD 201



OMD 201DC	DC VOLTMETER AND AMMETER
OMD 201PWR	AC NETWORK ANALYSER
OMD 201PM	PROCESS MONITOR
OMD 201OHM	OHMMETER
OMD 201RTD	THERMOMETER FOR Pt/Ni
OMD 201T/C	THERMOMETER FOR THERMOCOUPLES
OMD 201DU	DISPLAY UNIT FOR LINEAR POTENTIOMETERS
OMD 201UQC	UNIVERSAL COUNTER FREQUENCY METER
OMD 201RS	DATA DISPLAY

Description

The OMD 201 model series are large programmable displays, which are produced in many designs.

The instrument is based on an 8-bit processor and a precise A/D converter, that secures high accuracy, stability and easy operation of the instrument. Displays are designed for indoor and outdoor use with IP64 protection.

Displays are suitable for projection of measured data in productions lines and operations with legibility up to 80 m.

Holder for wall mounting applications may be supplied on request.

Operation

The instrument is set and controlled by four control keys located on a separate keyboard (5 m cable) or by remote IR control. All programmable settings of the instrument are realised in two adjusting regimes.

Configuration menu (hereinafter referred to as CM) is protected by an optional number code and contains complete instrument setting.

User menu may contain arbitrary programming settings defined in „CM“ with another selective restriction (see, change)

All settings are stored in the EEPROM memory (they hold even after the instrument is switched off).

The measured units may be projected on the 6 digit display.

Extension

Excitation is suitable for feeding of sensors and transmitters. It has a galvanic isolation with continuously adjustable value in the range of 2...24 VDC.

Comparators are assigned to monitor two limit values with relay output. The limits have adjustable hysteresis within the full range of the display as well as selectable delay of the switch-on in the range of 0...99,9 s. Reaching the preset limits is signalled by LED and simultaneously by the switch-on of the relevant relay.

Data outputs are for their rate and accuracy suitable for transmission of the measured data for further projection or directly into the control systems. We offer an isolated RS232 and RS485 with the ASCII protocol.

- 4/6 digit programmable projection
- Three-color LED, digit height 57; 100; 125 mm
- Digital filter, Tare
- Power supply 230 VAC

Extension

- Dual comparator • Excitation • Data output • Analog output
- Power supply 24/110 VAC, 10...30 VDC

Analog outputs will find their place in applications where further evaluating or processing of measured data is required in external devices. We offer universal analog output with the option of selection of the type of output - voltage/current. The value of analog output corresponds with the displayed data and its type and range are selectable in CM.

Standard functions

PROGRAMMABLE PROJECTION

Setting: manual, in „CM“ optional projection on the display may be set for values of the input signal

Setting (UQC): measuring mode 2x counter (UP/DW, IRC)/2x frequency/stopwatch/watch with adjustable calibration coefficient, time base and projection

Projection: -999...9999/-99999...999999, user-adjustable display color also with measurign units (red-green-orange)

COMPENSATION

of conduct (RTD): in „CM“ it is possible to perform compensation for 2-wire connection of conduct in probe (RTD): internal connection (conduct resistance in measuring head)

of CJC (T/C): manual or automatic, in „CM“ it is possible to perform selection of the type of thermocouple and compensation of cold junctions, which is adjustable or automatic (temperature at the input brackets)

DIGITAL FILTERS

Radius of insensitiveness: band of suppressed change of measured value

Exponen. průměr (UQC): z 2...100 measurements

n-th value (UQC): z 2...100 measurements

Filtration constant (UQC): limiting maximum input frequency, suppressing interfering impulses 10 Hz...2 kHz

FUNCTIONS

Preset (UQC): initial non-zero value, which is always read after resetting the instrument to zero

Summation (UQC): registration of the number upon shift operation

Pre-division constant (UQC): 1/10/60/100/1 000/3 600

Rounding: setting the projection step for display

Tare: resetting display upon non-zero input signal

EXTERNAL CONTROL

Hold: display/instrument blocking

Lock: control keys blocking

Instrument setting: 4-key keyboard with 5 m cable or remote IR control

Technical data

PROJECTION

Display: 4 (100/125 mm) or 6 digit (57/100/125 mm)
 Three-color LED - red/green/orange
Decimal point: adjustable - in programming mode
Brightness: adjustable - in programming mode

INSTRUMENT ACCURACY

TC: 100 ppm/°C
Accuracy: ±0,15% of range + 1 digit
 ±0,2% of range + 1 digit (OHM, PWR, RTD, T/C, DU)
 ±0,01% of range + 1 digit (UC)
Rate: 1,3...40 measurements/s, 0,6...5 measurements/s (PWR)
Overload capacity: 10x (t < 30 ms) - not for >300 V and 5A; 2x
Measuring modes (PWR): voltage (V_{RMS}), current (A_{RMS}), real power (W), frequency (Hz) and with calculation of Q, S, cos φ
Resolution: 0,1 °C (RTD), 1 °C (T/C)
Functions (UQC): data backup, time backup, preset
Input filters (UQC): filtration constant, rounding
Time base (UQC): 0,05...50 s
Calibration constant (UQC): 0,00001...999999
Filtration constant (UQC): 0...2 kHz
Presetting (UQC): 0...999999
Input (RS): adjustable, RS 232 i RS 485, parameters are identical with „Data output“
Watch-dog: reset after 1,2 s
Functions: HOLD, LOCK, digital filters, tare
Calibration: at 25 °C and 40% r.h.

COMPARATOR

Type: digital, adjustable in programming mode, contact switch-on < 30 ms
Limits 1 and 2: -999...3999
Hysteresis: 0...999
Delay: 0...99,9 s
Output: 2 relays with switching contact (250 VAC/30 VDC, 3 A)

DATA OUTPUTS

Data format: 8 bit + no parity + 1 stop bit (ASCII)
 7 bit + even parity + 1 stop bit (DIN Messbus)
Rate: 600...115 200 Baud
RS 232: isolated
RS 485: isolated, addressing (max. 31 instruments)

ANALOG OUTPUTS

Type: isolated, programmable with resolution of max. 10 000 points, analog output corresponds with the displayed data, type and range are selectable in CM
Non-linearity: 0,2% of range
TC: 100 ppm/°C
Rate: response to change of value < 40 ms
Ranges: 0...2/5/10 V, 0...5 mA, 0/4...20 mA (comp. < 600 Ω)

EXCITATION

Adjustable: 2...24 VDC/50 mA, isolated **DC, PM, UQC**

POWER SUPPLY

24, 110, 230 VAC, 50/60 Hz, ±10%, 15 VA
 10...30 VDC/max. 2 A, isolated
Power supply is protected by a fuse inside the instrument

MECHANIC PROPERTIES

Material: anodized aluminum, black
Dimensions: in mm

LED	length	height	depth	cutout
57	372	116	88	364 x 108
100-4	465	181	88	457 x 173
100-6	647	181	88	639 x 173
125-4	539	237	88	531 x 228
125-6	754	237	88	746 x 228

OPERATING CONDITIONS

Connection: connectors, conductor section < 2,5 mm²
Stabilization period: within 15 minutes after switch-on
Working temperature: 0 °...60 °C, (Storage: -10 °...85 °C)
Protection: IP64
Construction: safety class I
El. safety: EN 61010-1, A2
Overvoltage category: for pollution degree II
 II - instrument power supply, relay output (300 V)
 II - input, output (300 V)
EMC: EN 61000-3-2+A12; EN 61000-4-2, 3, 4, 5, 8, 11; EN 55022, A1, A2

Measuring ranges

	DC	PWR	PWR	PM	OHM	RTD	T/C	DU	UQC	RS
w/o				0/4...20 mA, 0...2/5/10 V		-99,9°...399,9°C	J, K, T, E, B, S, R, N	potentiometer > 500 Ω	TTL, NPN/PNP < 100 kHz	RS 232/485
A		0...10 V			0...0,4/4/40 kΩ	Pt 100/500/1000 (EU)				
B		0...30 V			0...10/100 kΩ, 5...105Ω	Pt 100/500/1000 (US)				
C		0...60 V				Ni 1 000/10 000 (5000)				
D		0...100 V				Ni 1 000/10 000 (6180)				
E										
F										
G										
H			0...60 mV							
I	0...0,4/1/5 A									
J			0...150 mV							
K			0...300 mV							
L			0...39,99 mA							
M			0...399,9 mA							
N			0...1 A							
P			0...5 A							
R										
S		0...150 V								
T		0...250 V								
U	0...60/150/300 mV, 0...4/40/400 V	0...450 V								
Z	on request	on request	on request	on request	on request					

Connection

To preserve the IP65 protection the display connection is realized through bushings directly to terminal board inside the instrument.

Order code

OMD 201

Type

D	C
P	M
O	H	M
P	W	R
R	T	D
T	C
D	U
U	Q	C
R	S

Order code shall not include blank spaces!

Power supply	24 VAC/50 Hz 230 VAC/50 Hz 110 VAC/50 Hz 10...30 VDC, isolated	0 1 3 4			
Measuring range, see table „Measuring ranges“		?			
Comparators	no yes	0 1			
Output	none Analog RS 232 RS 485	0 1 2 3			
Excitation	no yes	0 1			
Digit height	57 mm 100 mm 125 mm	1 2 3			
Number of digits	4 digits (100/125 mm) 6 digits	1 3			
Display color	red green	1 2			